

Feature Rich, Simple to Use, Icom Sets Another Benchmark

Optional COMMANDMIC™,
HM-195B



New Intuitive User Interface



Active Noise Cancelling



**10W Loud Audio, Public Address
and Foghorn**



**Optional COMMANDMIC™ HM-195B/SW
for 2nd Station/Intercom**



**Built-in Class D DSC
(Meets ITU-R M493-13)**



**IPX7 Waterproof Protection
(1m depth for 30 minutes)**



**Common NMEA Interface
for GPS/NAV Connection**



**MarineCommander™ and
MA-500TR compatible**



AquaQuake™ Function



Also available in super white version.

New Intuitive User Interface

The new menu system provides easy and intuitive operation. The bottom line of the dot-matrix display shows the software key functions which can be toggled with the left and right buttons. The directional keypad allows you to perform various operations and settings.

Active Noise Cancelling

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. Hear and be heard more clearly.

10W Loud Audio, Public Address and Foghorn

The IC-M423 has a built-in 10W amplifier that increases the audio output from additional external speaker. The public address function allows you to make an announcement from the microphone like a loud speaker, and the foghorn can also be emitted from the additional external speaker.

Built-in Class D DSC

The built-in DSC watch function monitors Ch. 70 (DSC channel) activity, even while you are receiving another channel. DSC functions include: distress, individual, group, all ships, urgency, safety, position request/report, polling request and DSC test calls.

Optional COMMANDMIC™ HM-195B/SW

The optional COMMANDMIC, HM-195B/SW makes it convenient for using the IC-M423 from a separate cabin or tower. All functions of the IC-M423 can be controlled from the COMMANDMIC and can be used as an intercom with the IC-M423.

Common NMEA Interface

When connected to an external GPS receiver, current position and time are shown on the IC-M423's display. When receiving position information from another vessel, the IC-M423 can transfer it to a navigational device via NMEA 0183 connectivity.

AIS Target Call with MA-500TR

When connected to the optional MA-500TR Class B AIS transponder, the AIS target call function allows you to make an individual DSC call without having to manually input a MMSI number.

And More

- MarineCommander™ compatible
- AquaQuake™ draining function
- IPX7 waterproof protection (1m depth for 30 minutes)
- Dual/tri-watch function for monitoring Ch.16 and/or call channel
- Priority and normal scan
- Black and super white versions available.

Supplied accessories:

- Hand microphone, HM-196B/SW
- DC power cable
- Mounting bracket kit

SPECIFICATIONS

| GENERAL | | |
|--|-----------------------------|--|
| Frequency range | Tx Rx CH70 | 156.000–161.450MHz 156.000–163.425MHz 156.525MHz |
| Usable channels | | INT, USA* channels * Available depending on version |
| Type of emission | | 16K0G3E (FM), 16K0G2B (DSC) |
| Power supply requirement | | 13.8V DC nominal (10.8–15.6V DC) |
| Current drain (at 12.0V DC) | Tx Rx AF max. (RX SP ON) | 5.5A 5.0A (External speaker) |
| Operating temperature range | | –20°C to +60°C |
| Antenna impedance | | 50Ω (SO-239) |
| Dimensions (W×H×D) (projections not included) | | 180×82×119.9mm |
| Weight (approx.) | | 1.2kg |
| NMEA in/out formats | | RMC, GGA, GNS, GLL, DSC, DSE |

| TRANSMITTER | | |
|----------------------------|--|-------------------|
| Output power (at 12.0V DC) | | 25W, 1W |
| Max. frequency deviation | | ±5.0kHz |
| Frequency stability | | Less than ±1.5kHz |
| Spurious emissions | | Less than 0.25μW |

| RECEIVER | | |
|--|-------------|--|
| Intermediate frequency | Main DSC | 21.700MHz/450kHz (1st/2nd) 30.875MHz/450kHz (1st/2nd) |
| Sensitivity | Main DSC | –5dBμ emf typ. (20dB SINAD) –4dBμ emf typ. (1% BER) |
| Squelch sensitivity | Main | Less than –2dBμ emf |
| Adjacent channel selectivity | Main DSC | More than 70dB More than 73dBμ emf (1% BER) |
| Spurious response | Main DSC | More than 70dB More than 73dBμ emf (1% BER) |
| Intermodulation | Main DSC | More than 68dB More than 68dBμ emf (1% BER) |
| Hum and noise | | More than 40dB |
| Audio output power (at 10% distortion, 4Ω load) | | More than 10W (Ext. speaker) |

Measurements made in accordance with EN 301 025-2, -3. All stated specifications are subject to change without notice or obligation.

Applicable IP Rating

| Ingress Protection Standard | |
|-----------------------------|------------------------------|
| Water | IPX7 (Waterproof protection) |

OPTIONS

COMMANDMIC™

HM-195B
(Black)

HM-195SW
(Super white)

Supplied accessories

- 6.1m (20ft) of cable
- Microphone hanger
- Mounting base for connector

EXTENSION CABLE for COMMANDMIC, HM-195B/SW

OPC-1541
6.1m (20ft) extension cable.
Up to two cables available.

FLUSH MOUNT KIT

MB-132

CLASS B AIS TRANSPONDER

MA-500TR

HM-196B/SW
SPEAKER-
MICROPHONE
Same as supplied.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia, Japan and/or other countries. COMMANDMIC, MarineCommander and AQUAQUAKE are trademarks of Icom Inc. (Japan). All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Blacksale House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone : +44 (0) 1227 741741
Fax : +44 (0) 1227 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone : +49 (6196) 76685-0
Fax : +49 (6196) 76685-50
E-mail : info@icom-europe.com
URL : <http://www.icomeurope.com>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindjonec des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 590 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska

81-850 Sopot, ul. 3 Maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolka@icompolka.com.pl
URL : <http://www.icompolka.com.pl>